

G24A2718 en

Product data

algemeen

| | |
|--|-------------|
| Reference No. | G24A2718 en |
| Mat. thickness mm | 2.50 |
| RAL color | 9006 |
| Load / kg | 425 |
| load indication at speed | 20 km/h |
| Recommended tyre size | 5.00-8 |
| Ø Mittenloch (A), Ø Bolzenlochkreis (B) und Bolzenlochzahl (C) | 60/100/4 |
| (A) Diameter centre hole mm | 60 |
| (B) Pitch circle diameter mm | 100 |
| (C) Number of studholes | 4 |
| (C) Stud hole diameter mm | 13.5 |
| Gatvorm | 600 |
| Rim size | 3.00Dx8 |
| Mat. thickness mm | 2.00 |
| RAL color | 3002 |
| Load / kg | 725 |
| load indication at speed | 20 km/h |
| Recommended tyre size | 5.00-8 |
| Ø Mittenloch (A), Ø Bolzenlochkreis (B) und Bolzenlochzahl (C) | 60/100/4 |
| (A) Diameter centre hole mm | 60 |
| (B) Pitch circle diameter mm | 100 |
| (C) Number of studholes | 4 |
| (C) Stud hole diameter mm | 13.5 |
| Gatvorm | 600 |
| Rim size | 3.00Dx8 |